


1000BASE-T SINGLE & DUAL PORT TRANSFORMER MODULES

Ruggedized

inRCORE
INRCORE FAMILY OF BRANDS



- Compliant with IEEE 802.3 standards
- 350pH OCL with 8mA DC bias at extended temperatures
- Dielectric Withstanding Voltage (DWV): 1500 Vrms
- Storage Temperature: -55°C to +125°C
- Operating Temperature:
1000B-5001/5002/5003: -40°C to +85°C
1000B-5001X/5002X/5003X: -55°C to +125°C
- Epoxy Encapsulated Package
- Lead Finish: Sn63/Pb37
- Moisture Sensitivity Level: 3

Electrical Specifications @ 25°C

Part Number	Insertion Loss (dB MAX)				Return Loss (dB MIN)				Crosstalk (dB MIN)			CM to CM Rejection (dB MIN)			DM to CM Rejection (dB MIN)		
	0.10 MHz	30 MHz	60 MHz	100 MHz	30 MHz	60 MHz	80 MHz	100 MHz	30 MHz	60 MHz	100 MHz	30 MHz	60 MHz	100 MHz	30 MHz	60 MHz	100 MHz
1000B-5001	1.2	1.2	1.2	1.2	18	12	10	8	43	37	33	40	35	30	43	37	30
1000B-5001X	1.4	1.4	1.4	1.4	18	12	10	8	43	37	33	40	35	30	43	37	33
1000B-5002	1.2	1.2	1.2	1.2	18	14	12	10	43	37	33	40	35	30	43	37	33
1000B-5002X	1.2	1.2	1.2	1.2	18	14	12	10	43	37	33	40	35	30	43	37	33
1000B-5003	1.2	1.2	1.2	1.2	18	14	11	9	43	37	33	40	35	30	43	37	33
1000B-5003X	1.2	1.2	1.2	1.2	18	14	11	9	43	37	33	40	35	30	43	37	33

NOTES:


- Add suffix "NL" for RoHS compliant version; i.e. 1000B-5001 becomes **1000B-5001NL**. (For NL version of 5003/5003X, MSL = 4) NL parts have 100% SN Lead Finish.
- For Tape & Reel packaging, add "T" suffix at the end of the part number: i.e. **1000B-5001NLT**

Mechanicals

Electrical Schematics


1000B-5001/X

Dimensions: inch [mm]
Tolerance (unless otherwise specified): ±0.010 [0.25]



LEGEND

C H I P S I D E
 T d Mx Mx Mx Mx
 M E D I A S I D E
 All channels are in phase between input and output



Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. inRCORE, LLC. All rights reserved.

M1061.C (8JUN23)

Ruggedized



Dimensions: inch [mm]
Tolerance (unless otherwise specified): ± 0.010 [0.25]



LEGEND


MEDIA SIDE

channels are in use between input and output

Dimensions: inch [mm]
Tolerance (unless otherwise specified): ± 0.010 [0.25]



LEGEND




M1061.C (8JUN23)

1000BASE-T SINGLE & DUAL PORT
TRANSFORMER MODULES

Ruggedized

Recommended Reflow Profile (Based on J-STD-020D)



T_{smin} (°C)	T_{smax} (°C)	T_L (°C)	T_p (°C MAX)	t_s (s)	t_L (s)	t_p (s MAX)	Ramp-up rate (T_L to T_p)	Ramp-down rate (T_p to T_L)	Time 25°C to peak temperature (s MAX)
Tin/Lead Profile									
100	150	183	235	60 - 120	60 - 150	20	3°C/s MAX	6°C/s MAX	360
Non-Lead Profile									
150	200	217	245	60 - 120	60 - 150	30	3°C/s MAX	6°C/s MAX	480

NOTES:

1. All temperatures measured on the package leads.
2. Maximum number of reflow cycles not to exceed 2.
3. Reflow cycle applies only to surface mount parts.



iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

www.iNRCORE.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. iNRCORE, LLC. All rights reserved.

M1061.C (8JUN23)