

Class 11, manual starter, 0.18-0.25 Amps, NEMA 1,



Figure similar

| | |
|---|----------------|
| product brand name | Class 11 |
| design of the product | Manual Starter |
| General technical data | |
| ambient temperature [°F] | |
| • during storage | 122 ... 176 °F |
| • during operation | 68 ... 140 °F |
| ambient temperature | |
| • during storage | 50 ... 80 °C |
| • during operation | 20 ... 60 °C |
| number of poles for main current circuit | 3 |
| Contactor | |
| mechanical service life (switching cycles) of the main contacts typical | 100000 |
| Coil | |
| type of voltage of the control supply voltage | n.a. |
| Overload relay | |
| adjustable current response value current of the current-dependent overload release | 0.25 A |
| Mounting/wiring | |
| fastening method | wall mounting |
| Short-circuit current rating | |
| design of the short-circuit trip | magnetic |
| Certificates/ approvals | |
| certificate of suitability | UL |
| Further information | |

Industrial Controls - Product Overview (Catalogs, Brochures,...)

www.usa.siemens.com/iccatalog

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:11CD3B>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/US/en/ps/US2:11CD3B>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:11CD3B&lang=en

Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:11CD3B/certificate>

last modified:

2/1/2021