

FLKM-KS40/AO16/YCS - Passive module



2314260

<https://www.phoenixcontact.com/us/products/2314260>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

16-channel analog module with a screw connection and two 40-pos. system connections. Suitable for the Yokogawa AA1543 card.



Your advantages

- For AAI 543 analog module

Commercial data

Item number	2314260
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK218N
Catalog page	Page 521 (C-5-2017)
GTIN	4046356143776
Weight per piece (including packing)	273.9 g
Weight per piece (excluding packing)	206.92 g
Customs tariff number	85369010
Country of origin	DE

2314260

<https://www.phoenixcontact.com/us/products/2314260>

Technical data

Product properties

Product type	Interface module
No. of channels	16

Data management status

Article revision	05
------------------	----

Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

Electrical properties

Operating voltage (DC)	≤ 30 V DC
Current (per branch)	≤ 0.1 A

Air clearances and creepage distances

Rated insulation voltage	50 V
Rated surge voltage	0.5 kV (1.2/50 μs)

Supported controller YOKOGAWA CS3000 CentumVP

Suitable I/O card	AAI543
-------------------	--------

Supported controller YOKOGAWA STARDOM

Suitable I/O card	NFAI543
-------------------	---------

Connection data

Connection 1 (control level)

Connection method	Yokogawa KS-compatible
Number of connections	2
Number of positions	40
Note	Usable system cables: Phoenix Contact YUC40, Yokogawa KS1
Tightening torque	0.5 Nm
Pitch	2.54 mm

Connection 2 (field level)

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Number of positions	48
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross-section rigid (2 conductors with same cross section)	0.2 mm ² ... 1.5 mm ²
	0.2 mm ² ... 2.5 mm ²

FLKM-KS40/AO16/YCS - Passive module



2314260

<https://www.phoenixcontact.com/us/products/2314260>

Conductor cross section flexible	0.25 mm ² ... 1.5 mm ² (Ferrule without plastic sleeve)
	0.25 mm ² ... 2.5 mm ² (Ferrule with plastic sleeve)
Conductor cross section flexible (2 conductors with same cross section)	0.2 mm ² ... 1.5 mm ²
	0.25 mm ² ... 0.75 mm ² (Ferrule without plastic sleeve)
	0.5 mm ² ... 0.5 mm ² (TWIN ferrule with plastic sleeve)
Conductor cross section AWG	24 ... 12
Tightening torque	0.5 Nm ... 0.6 Nm
Pitch	5.08 mm

Connection 3 (HART connector)

Connection method	HART connector
Number of connections	1
Number of positions	26
Pitch	1.27 mm

Signaling

Status display present	No
------------------------	----

Dimensions

Item dimensions

Width	107.5 mm
Height	125.4 mm
Depth	65.9 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection (Module)	IP00
Degree of protection (Installation location)	≤ IP54
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Altitude	≤ 2000 m

Approvals

UKCA

Certificate	UKCA-compliant
-------------	----------------

Standards and regulations

Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

Mounting

Mounting type	DIN rail mounting
Mounting position	any

FLKM-KS40/AO16/YCS - Passive module



2314260

<https://www.phoenixcontact.com/us/products/2314260>

Notes

Notes on operation

For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

FLKM-KS40/AO16/YCS - Passive module




2314260

<https://www.phoenixcontact.com/us/products/2314260>

Drawings

Circuit diagram




FLKM-KS40/AO16/YCS - Passive module



2314260

<https://www.phoenixcontact.com/us/products/2314260>



FLKM-KS40/AO16/YCS - Passive module



2314260

<https://www.phoenixcontact.com/us/products/2314260>

Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-12.0	27141152
ECLASS-13.0	27141152

ETIM

ETIM 9.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

FLKM-KS40/AO16/YCS - Passive module



2314260

<https://www.phoenixcontact.com/us/products/2314260>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	e3af7f49-5382-4fff-8b09-45718581eebc

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com