






NOTES:

1. PLUG FINGER SAME AS 290
2. PLUG FINGER, HANDLE, STRAIN RELIEF, AND SCREWS ARE SHIPPED UNASSEMBLED.
3. ASSEMBLE STRAIN RELIEF TO HANDLE BEFORE INSERTING CABLE.
4. THIS PRODUCT IS RoHS COMPLIANT.

PARTNUMBER	PART REV	RECOMMENDED STRAIN RELIEF CABLE RANGE
290F	0A	Ø 0.220 - Ø 0.190
290FL	0A	Ø 0.250 - Ø 0.220

CUSTOMER DRAWING

					UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES [mm] - TWO PLACE DECIMALS ±0.02 [0.5] - THREE PLACE DECIMALS ±0.005 [0.13]	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
						SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *	
						FINISH *			MATERIAL *		
						SPEC No. *			SPEC No. *		
						FIRST USED ON *		SCALE 5:4		Switchcraft®	
						DATE DRAWN	BY	CHKD	APVD		
0A	PRELIMINARY	6/19/17	*	*		6/19/17	AB	AB 6/19/17	*	*	
REV	ECO NUMBER	DATE	BY	APVD	NAME			PART No.		REV	
REVISIONS					DO NOT SCALE DRAWING		290 FLEX, RoHS		290F - 290FL		0A

SolidWorks CAD File

