

LC DUPLEX PC SINGLEMODE ADAPTOR
 ZIRCONIA ALIGNMENT SLEEVE

Packaging
 100


Series
 LC

Issue
 12 11 02

Page
 1 / 2

Adaptor : color BLUE

Duplex



Original dimensions in mm [inch]

LC DUPLEX PC SINGLEMODE ADAPTOR
 ZIRCONIA ALIGNMENT SLEEVE

 Packaging
 100

 Series
 LC

 Issue
 12 11 02

 Page
 2 / 2

Adaptor : color BLUE

Duplex

GENERAL

- ❑ **TYPE** IEC 61754-20 (LC)
RJ-45 latching system
Receptacle color : BLUE
- ❑ **MOUNTING** Snap-in mounting
Max. panel thickness 1.7 mm
- ❑ **ALIGNMENT SLEEVE** Zirconia

CHARACTERISTICS (Depending on fibre or cable construction)

- ❑ **MATERIAL** Plastic molded : Material in accordance with TELCORDIA GR-326 CORE
Inflammability V0 (UL 94)
- ❑ **MECHANICAL** Durability 200 cycles
- ❑ **ENVIRONMENTAL** Storage temperature range -40°C to +85°C
Operating temperature range -40°C to +70°C
- ❑ **PROOF TEST** Straight pull 68 N
Side pull 23 N
- ❑ **VIBRATION TEST** 10 to 55 Hz, 1,5 mm (peak to peak), 2 Hr/axis

(Performance and specification : see document **GEN - F727 001**)