



NOTES:
 INSULATION RESESTANCE(MIN.):1000MOHMS
 CURRENT RATING(MAX.): 3amp AC/DC
 WITHSTANDING VOLTAGE:1000VAC
 CONTACT RESISTANCE(MAX.)30m chms
 OPERATION TEMPERATURE:-55°~+105°
 MATERIAL:
 CONTACT: BRONZE
 INSULATION: PBT+30%GLASS FIBER.U.L 94V-0
 SHELL;STEEL
 NOTICE: THE DIMENSION MAKED WITH " * " MUST BE CONTROLLED BY QC.

PARTS DIMENSION TABLE

parts no.	DIM. a	DIM. b	inner thread
1	4.8	11.8	4#40
2	5.8	12.0	4#40
3	4.8	11.8	M3
4	5.8	11.8	M3
5	4.8	11.8	M2.6
6	5.8	12.0	M2.6
7	6.0	12.0	4#40

POS.	A	B	C	D	E	G
9	30.80	24.99	16.34	19.00	15.60	4.0/4.6
15	39.20	33.32	24.76	27.70	24.60	4.0/4.6
25	53.05	47.04	38.33	41.10	38.10	4.0/4.6
37	69.50	63.50	54.89	57.30	54.30	4.0/4.6

UNLESS TOLERANCE		DRAW BY: HANK	2022.05.28	东莞市赢海电子有限公司
GENERAL	ANGLE			
X ± 0.30	X° ± 3'	DESIGN BY: HANK	2022.05.28	PAPT NO: C970246 ITEM : GDP37F-180
.X ± 0.25	.X° ± 2'	CHECK BY:		
.XX ± 0.20	.XX° ± 1'	APPROVE BY:		
.XXX ± 0.15	.XXX° ± 0.5'	SCALE	SHEET UNIT	DRW NO: HP20220531
		1:1	1/1	mm
				REV: 1.3