



SPECIFICATION

1. Rating: DC 12V 0.3A
2. Travel: 2 mm
3. Function: 4P2T
4. Contact Resistance: ≤70mΩMAX
5. Operating Force: 200±80gf
6. Life test: 10,000 cycles

电话 : 0769-82320511-867

					TOLERANCE UNLESS SPECIFIED							
5	MS42D02 TERMINAL	BRASS	1	Ag PLATED	UP TO 5mm: ±0.1	ANGULAR	A1	2017.05.11	△????3.2?3.4		GYW	
4	MS42D02 CONTACT	BERYLLUM	4	Ag PLATED	ABOVE 5mm: ±0.2	±1°	NO	DATE	REVISIONS		BY APPD	
3	MS42D02 CASE	PA6T/LCP	1	BLACK	TITLE:MINI SLIDE SWITCH		UNIT : MM		ROHS COMPLIANT	DWN		
2	MS42D02 COVER	SUS	1	Ni PLATED	MODEL: MK-42D02G2-B		SCALE: 5:1			CHK'D		
1	MS42D02 KNOB	PA6T+PA66	1	BLACK	HAOYU(HONGKONG)LIMITED 皓宇(香港)有限公司						APPD	
NO.	PART NAME	MATERIAL	QTY	FINISHING							PRO.AGL:	